



ULTRA® MAX II Premium

The Pro's choice for Painting Applications



www.graco.be



HD Prime Valve
Improved
Control Board

PROFESSIONAL ADVANTAGES


- Easy to use, to service and to transport
- Applies most architectural coatings
- Industry exclusive technologies

MATERIALS

Acrylic - Primers - Emulsions - Waterborne paint - Solvent based paint

Professional Airless Applications

ULTRA® MAX II 695 Premium - ULTRA® MAX II 795 Premium - ULTRA® MAX II 1095 Premium





ULTRA[®] MAX II

Premium Series

Ultra[®] Max II 1095 Premium Advanced Features



1 Unscrew paint line



2 Open latch that opens front cover



3 Remove pin. Pump lower is free.



EXCLUSIVE PUMP ATTACHMENT
Remove and replace your entire pump lower:
On the job - without any tools - in seconds

ULTRA[®] MAX II Premium SPECIFICATIONS

www.pro-connect.eu

Part Numbers:

for Europe - 220 V
for Italy, Denmark, Switzerland - 220 V
for UK - 110 V

	Ultra Max II PREMIUM 695	Ultra Max II PREMIUM 795	Ultra Max II PREMIUM 1095 PROCONNECT
Max. Tip Size:	1 gun 0.029" 2 guns 0.017"	0.031" 0.021"	0.035" 0.025"
Flow - l/min. (gpm)	3.0 (0.75)	3.6 (0.95)	4.1 (1.15)
Max. pressure - bar (PSI)	230 (3300)	230 (3300)	230 (3300)
Weight - kg (lbs)	43 (94)	45 (98)	55 (120)
SmartControl™ version	2.0	2.0	2.0
Motor Type	DC Brushless	DC Brushless	DC Brushless
Motor rating - kW	1.3	1.5	1.65
Generator requirements - kW	5	5	5

Ships complete and ready to spray!

Accessory box standard: SmartControl™, WatchDog™, AutoClean™, ProConnect™ (on 1095 only), Contractor™ II gun with Handtite™ RAC X guard and tips PAA517, PAA625 + PAA621, 238358 BlueMax™ II whip hose 3/16" x 0.90 m, 240794 BlueMax II hose 1/4" x 15 m, 238358 BlueMax II whip hose 3/16" x 0.90 m, 206994 TSL™ 0.25 l, 197193 universal hammer tool, 111733 adjustable wrench.

Motor & SmartControl™ 2.0
The unit's brain controls the very strong performing brushless DC motor.
- Save energy! SmartControl makes the motor turn only if pressure is needed
- Adjusts the pressure immediately to the tip size and maintains very accurately the stalled pressure
- Digital display with pressure rating, liter counter and error coding: ALL FROM THE PUSH OF ONE BUTTON

WatchDog™
PROTECTS YOUR PUMP.
The WatchDog shuts off the pump immediately when material runs out.

AutoClean™ 2 + Heavy Duty Prime Valve
Now fully automated.
Connect your gun and switch the HD prime valve to the AutoClean position. The system will do the rest: while you start other cleaning activities, the system cleans gun, hose, filters and unit independently!

Endurance™ Pump
Graco's proven Piston Pump, Handtight™ inlet tube and pump lower: clean your valves in minutes without special tools on the job!

Easy Out™ Filter system



ACCESSORIES

- Guns**
288475 Contractor™ gun, 2-finger, RAC X guard & 517 tip
288425 Contractor™ gun, 4-finger, RAC X guard & 517 tip
288477 Contractor gun, 4-finger, RAC™5 guard, no tip

- Easy Out™ Gun Filters**
287032 Easy Out™ gun filter, 60 Mesh x 1
287033 Easy Out™ gun filter, 100 Mesh x 1
287034 Kit: 60 + 100 Mesh (one each)

- Easy Out™ Pump Filters**
244071 30 Mesh, grey
244067 60 Mesh, black
244068 100 Mesh, blue
244069 200 Mesh, red

- BlueMax™ II Hoses**
240794 1/4" x 15 m
241272 1/4" x 20 m
223771 1/4" x 30 m
240797 3/8" x 15 m
241275 3/8" x 30 m

- Whips (230 bar)**
238358 3/16" x 0.9 m
238959 3/16" x 1.4 m
238359 3/16" x 1.8 m

- Ultra[®] Max II Kit**
288491 Contractor™ gun, 1/4" x 15m hose, 1/4" x 0.9m whip hose, RACX guard & 621 tip
288498 Contractor™ gun, 1/4" x 15m hose, 1/4" x 0.9m whip hose, RAC5 guard & 517 tip

- 1095 ProConnect Pump**
287513 Pump Lower

- PRO Tip Extensions**
with RAC X Guard
287019 25 cm
287020 40 cm
287021 50 cm
287022 75 cm

- CleanShot™ Pole Gun**
287026 90 cm w/ RAC X
287027 180 cm w/ RAC X

- Rollers Exterior (complete)**
6880095 30 cm fixed
098084 90-180 cm telescopic
098085 45-90 cm telescopic

- Tips & Guards**
FFAXXX Green RAC X™
Fine Finish Tip
PAAXXX Blue RAC X™
Professional Airless Tip
WA12XX RAC X WideRac,
for big surfaces
246215 RAC X guard

- Liquids**
206994 TSL™ 0.25 l
253574 Pump Armor™ 1 l